

5 Lever Mortice Deadlock

3G114E

Application:

- Kitemarked BS3621 deadlock. Approved by insurance companies and the Police
- For timber door hinged on the left or the right
- Keys are suitable for use on doors up to 50mm thick

Operation:

- Deadbolt is locked or unlocked by key from either side

Specification:

Reference	3G114E
Case Size	67mm or 80mm
Backset	40mm or 53mm
Case	Silver powder coat
Forend	Stainless steel or brass
Box Strike Assembly	Painted to match forend
Deadbolt	Brass, with hardened steel rollers
Keying Groups	Standard differ or to pass (BP codes)
Keys supplied	Standard differ supplied with 3 keys. For locks to pass please specify number of keys required.
Key Blank Number	B-K722 (standard) B-K750 (RKS)
Cut Key Number	B-5LC standard
NB	Not suitable for master keying
Rebate Kit	B-3G114R (13mm, 19mm, 25mm)

Features:

- Force resistant, anti drill, anti-pick and anti-saw security features
- Available with square forend and striking plate
- 20mm bolt throw
- Can be supplied on patented RKS key section to prevent illicit copying of keys
- Can be supplied with either a single or double pole microswitch for alarm systems.
- Supplied with one plain escutcheon and one escutcheon with a cover plate, finished to match the faceplate/strike



Finishes:

- SC - Satin Chrome finish
- PL- Brass finish

Standards:

- Tested to BS3621:2007
- EN1634-1 assessed for use on 60 minute timber fire doors



Ordering Code Example:

- B-3G114E-PL-67 (Boxed)
- V-3G114E-SC-67 (Visi pack)
- B-3G114EDP-PL-67 (double pole microswitch)

