

FritsJurgens by Bellevue Architectural

SYSTEM M / M+ Concealed Pivot

MODEL SELECTOR

To ensure the desired door movement, System M / M+ is available in multiple versions depending upon the weight & width of the door. Using the chart on the next page you can easily select which model best matches your door specifications.

EXAMPLE

Use the model selector chart on the next page to determine your specific model required:

Door specifications: Width: 1600mm, weight 165kg.

The distance between the pivot point and the side of the door is 70mm

1. Check the door width **C = 1600 mm**
2. Determine the distance of pivot point to the latch side of the door: **C minus B = A: 1530mm**
3. Fill in the weight **KG = 165 kg**
4. On the following page, select the column 1500mm (A line), map the door weight 165Kg = [FJS/STM+70DSSS](#)

70mm Pivot point order code (STANDARD floor plate) Kit finish: SSS Kit finish: Black FJS/STM70AASSS FJS/STM70AASBK FJS/STM+70AASSS FJS/STM+70ASBK FJS/STM+70BSSS FJS/STM+70BSBK FJS/STM+70CSSS FJS/STM+70CSBK FJS/STM+70DSSS FJS/STM+70DSBK FJS/STM+70ESSS FJS/STM+70ESBK FJS/STM+70FSSS FJS/STM+70FSBK FJS/STM+70GSSS FJS/STM+70GSBK		70mm Pivot point order code (FLUSH floor plate) Kit finish: SSS Kit finish: Black FJS/STM70AAFSSS FJS/STM70AAFSBK FJS/STM+70AFSSS FJS/STM+70AFSBK FJS/STM+70BFSSS FJS/STM+70BFSBK FJS/STM+70CFSSS FJS/STM+70CFSBK FJS/STM+70DFSSS FJS/STM+70DFSBK FJS/STM+70EFSSS FJS/STM+70EFSBK FJS/STM+70FFSSS FJS/STM+70FFSBK FJS/STM+70GFSSS FJS/STM+70GFSBK	
40mm Pivot point order code (STANDARD floor plate) Kit finish: SSS Kit finish: Black FJS/STM40AASSS FJS/STM40AASBK FJS/STM+40AASSS FJS/STM+40ASBK FJS/STM+40BSSS FJS/STM+40BSBK FJS/STM+40CSSS FJS/STM+40CSBK FJS/STM+40DSSS FJS/STM+40DSBK FJS/STM+40ESSS FJS/STM+40ESBK FJS/STM+40FSSS FJS/STM+40FSBK FJS/STM+40GSSS FJS/STM+40GSBK		40mm Pivot point order code (FLUSH floor plate) Kit finish: SSS Kit finish: Black FJS/STM40AAFSSS FJS/STM40AAFSBK FJS/STM+40AFSSS FJS/STM+40AFSBK FJS/STM+40BFSSS FJS/STM+40BFSBK FJS/STM+40CFSSS FJS/STM+40CFSBK FJS/STM+40DFSSS FJS/STM+40DFSBK FJS/STM+40EFSSS FJS/STM+40EFSBK FJS/STM+40FFSSS FJS/STM+40FFSBK FJS/STM+40GFSSS FJS/STM+40GFSBK	



