Metlam Australia Pty Ltd 1300 METLAM sales@metlam.com.au www.metlam.com.au

TOILET PARTITION HARDWARE




106B

106B Gravity Hinge - Bolt Through

Specification

Material Diecast Zinc, Alloy ZP3 #304 Stainless Steel Shaft Nylon Inserts Finish Satin Chrome Plate Mounting Bolt Through Minimum Hinge Clearance For Lift-Off Hinges 30mm Specify 106B_LHHC_SCP: Left Hand, Hold Closed, Assists door to move towards Hold Closed position 106B_LHHO_SCP: Left Hand, Hold Closed, Assists door to move towards Hold Open position 106B_RHHO_SCP: Right Hand, Hold Closed, Assists door to move towards Hold Closed position 106B_RHHO_SCP: Right Hand, Hold Closed, Assists door to move towards Hold Open position Features Gravity-assisted door opening/door closing with lift-off capability. Load Rating 15Kg per hinge For optimum performance- 2 hinges per door up to 30Kgs For doors over 30Kg allow for 15Kg per hinge Note: 3H linges are available with or without fixings. Please nominate your requirements at the time of ordering . Disclaimer Gravity hinges contain no mechanical components. The functionality of these hinges can vary depending on the environment. When selecting this product, please view our Product Disclosure Statement in the Care and Maintenance Download below.		
Mounting Bolt Through Minimum Hinge Clearance For Lift-Off Hinges Specify 106B_LHHC_SCP: Left Hand, Hold Closed. Assists door to move towards Hold Closed position 106B_LHHO_SCP: Left Hand, Hold Open. Assists door to move towards Hold Closed position 106B_RHHC_SCP: Right Hand, Hold Closed. Assists door to move towards Hold Closed position 106B_RHHO_SCP: Right Hand, Hold Open. Assists door to move towards Hold Open position 106B_RHHO_SCP: Right Hand, Hold Open. Assists door to move towards Hold Open position Features Gravity-assisted door opening/door closing with lift-off capability. Load Rating 15Kg per hinge For optimum performance - 2 hinges per door up to 30Kgs For doors over 30Kg allow for 15Kg per hinge Note: 3 Hinges per door is recommended to prevent door bowing Note: All hinges are available with or without fixings. Please nominate your requirements at the time of ordering . Disclaimer Gravity hinges contain no mechanical components. The functionality of these hinges can vary depending on the environment.	Material	#304 Stainless Steel Shaft
Minimum Hinge Clearance For Lift-Off Hinges Specify 106B_LHHC_SCP: Left Hand, Hold Closed. Assists door to move towards Hold Closed position 106B_LHHO_SCP: Left Hand, Hold Open Assists door to move towards Hold Open position 106B_RHHC_SCP: Right Hand, Hold Open. Assists door to move towards Hold Closed position 106B_RHHO_SCP: Right Hand, Hold Open. Assists door to move towards Hold Open position Features Gravity-assisted door opening/door closing with lift-off capability. Load Rating 15Kg per hinge For optimum performance- 2 hinges per door up to 30Kgs For doors over 30Kg allow for 15Kg per hinge Note: 3 Hinges per door is recommended to prevent door bowing Note: All hinges are available with or without fixings. Please nominate your requirements at the time of ordering. Disclaimer Gravity hinges contain no mechanical components. The functionality of these hinges can vary depending on the environment.	Finish	Satin Chrome Plate
Clearance For Lift-Off Hinges Specify 106B_LHHC_SCP: Left Hand, Hold Closed. Assists door to move towards Hold Closed position 106B_LHHO_SCP: Left Hand, Hold Open. Assists door to move towards Hold Open position 106B_RHHC_SCP: Right Hand, Hold Closed. Assists door to move towards Hold Closed position 106B_RHHO_SCP: Right Hand, Hold Open. Assists door to move towards Hold Open position Features Gravity-assisted door opening/door closing with lift-off capability. Load Rating 15Kg per hinge For optimum performance- 2 hinges per door up to 30Kgs For doors over 30Kg allow for 15Kg per hinge Note: 3 Hinges per door is recommended to prevent door bowing Note: All hinges are available with or without fixings. Please nominate your requirements at the time of ordering. Disclaimer Gravity hinges contain no mechanical components. The functionality of these hinges can vary depending on the environment.	Mounting	Bolt Through
106B_LHHO_SCP: Left Hand, Hold Open. Assists door to move towards Hold Open position 106B_RHHC_SCP: Right Hand, Hold Closed. Assists door to move towards Hold Closed position 106B_RHHO_SCP: Right Hand, Hold Open. Assists door to move towards Hold Open position Features Gravity-assisted door opening/door closing with lift-off capability. Load Rating 15Kg per hinge For optimum performance - 2 hinges per door up to 30Kgs For doors over 30Kg allow for 15Kg per hinge Note: 3 Hinges per door is recommended to prevent door bowing Note: All hinges are available with or without fixings. Please nominate your requirements at the time of ordering . Disclaimer Gravity hinges contain no mechanical components. The functionality of these hinges can vary depending on the environment.	Clearance For	30mm
Load Rating 15Kg per hinge For optimum performance - 2 hinges per door up to 30Kgs For doors over 30Kg allow for 15Kg per hinge Note: 3 Hinges per door is recommended to prevent door bowing Note: All hinges are available with or without fixings. Please nominate your requirements at the time of ordering . Disclaimer Gravity hinges contain no mechanical components. The functionality of these hinges can vary depending on the environment.	Specify	106B_LHHO_SCP: Left Hand, Hold Open. Assists door to move towards Hold Open position 106B_RHHC_SCP: Right Hand, Hold Closed. Assists door to move towards Hold Closed position
For optimum performance - 2 hinges per door up to 30Kgs For doors over 30Kg allow for 15Kg per hinge Note: 3 Hinges per door is recommended to prevent door bowing Note: All hinges are available with or without fixings. Please nominate your requirements at the time of ordering. Disclaimer Gravity hinges contain no mechanical components. The functionality of these hinges can vary depending on the environment.	Features	Gravity-assisted door opening/door closing with lift-off capability.
2 hinges per door up to 30Kgs For doors over 30Kg allow for 15Kg per hinge Note: 3 Hinges per door is recommended to prevent door bowing Note: All hinges are available with or without fixings. Please nominate your requirements at the time of ordering. Disclaimer Gravity hinges contain no mechanical components. The functionality of these hinges can vary depending on the environment.	Load Rating	15Kg per hinge
Disclaimer Gravity hinges contain no mechanical components. The functionality of these hinges can vary depending on the environment.		2 hinges per door up to 30Kgs For doors over 30Kg allow for 15Kg per hinge
		Note: All hinges are available with or without fixings. Please nominate your requirements at the time of ordering .
	Disclaimer	





Downloads & Resources

Care & Maintenance

Care & Maintenance
Installation instructions
Associated Videos
Stainless Steel Cleaning & Maintenance
Accessibility and safety features of Metlam Australia Toilet Partition Hardware and how to use them
Troubleshooting your Metlam Australia Toilet Partition Hardware - Hinges