

SHOWER SEATS & SHOWER RELATED



ML_SK338_SS

Vertical Shower Grab Rail Kit - Combination of MLR338_SS and ML_HSK_CHROME

Specification

Material	#304 Stainless Steel Grab Rail, Chrome/Grey hand shower, Chrome 2.0m high pressure hose, Chrome Elbow and Grab Slider.
Finish	Satin Stainless Steel
Mounting	Concealed Fix - 78mmØ Mount
Dimensions	800mm C to C Grab Rail, 32mm Shower Kit
Features	Shower heads have MAXIMUM flow rate of 6 litres per minute, kits have watermark WMKT21090, hoses are standard pressure of 150-350Kpa as per AS/NZS 3662.2006 WELS: 5 Star - 6L/min
Notes	<p>* It is the responsibility of the installer to ensure that the surface/substrate that the unit is installed upon and the fixings used are suitable to withstand the weight bearing loads of the unit and if required as per AS1428 / Australian building code regulations.</p> <p>* Compliant with the Force Requirements within AS1428.1: 2021, Section 14.</p>



Downloads & Resources

- Care & Maintenance
- Installation instructions
- Associated Videos
- Stainless Steel Cleaning & Maintenance

The photographs and line drawings of the products presented above are representational only. Metlam Australia Pty Ltd reserves the right to, and from time to time, make changes and improvements in design and dimensions.