

Everything you need for cavity sliding doors



stainless steel range

- Minimum door thickness 32mm
- Cavity locks suit a 54mm standard hole
- 60mm backset
- Round and square models
- Passage and privacy functions available
- Supplied in visual display pack

Dimensions:

- **Round backplate:**
65mm diameter - internal diameter 50mm
- **Square backplate:**
65mm x 65mm - internal diameter 50mm
- **Fingerpull:**
24mm base diameter - 29mm top diameter
Recessed depth 21mm
Suits a 25mm diameter hole



SCD-PRI-RD privacy set
SS, PSS, BL finishes



SCD-PRI-RD privacy set
SS, PSS, BL finishes



SCD-PRI-SQ privacy set
SS, PSS, BL finishes



SCD-PRI-SQ privacy set
SS, PSS, BL finishes



SCD-PAS-RD passage set
SS, PSS, BL



SCD-PAS-SQ passage set
SS, PSS, BL



FINGERPULL-RD
BN, CP, BL



FINGERPULL-SQ
BN, CP, BL

Contemporary - Rectangular



FPCRECBL
BL



FPCRECSC
SC



FPCRECWH
WH

Traditional



FPREC
SC, CP, PB



FPRAD
SC, CP, PB

Stainless Steel



FPSQ1
SS, PSS



FPRD1
SS, PSS



FPSQ2
SS, PSS